

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C10L 1/30, 10/02, G09B 9/00, A62C 39/00	A1	(11) International Publication Number: WO 97/21790 (43) International Publication Date: 19 June 1997 (19.06.97)
(21) International Application Number: PCT/US96/19915 (22) International Filing Date: 11 December 1996 (11.12.96) (30) Priority Data: 08/570,053 11 December 1995 (11.12.95) US (71) Applicant: EXXON CHEMICAL PATENTS INC. [US/US]; 5200 Bayway Drive, Baytown, TX 77520-5200 (US). (72) Inventors: SCHREINER, James, L.; 17446 Kitzman, Cypress, TX 77429 (US). MOIR, Michael, E.; 523 Robin Drive, Corte Madera, CA 94925 (US). HOLMES-SMITH, Rupert, D.; 222 Hawktree Bay N.W., Calgary, Alberta T3G 2Z3 (CA). RUIGROK, Charles, F.; 105 Willow Farm Lane, Aurora, Ontario L4G 6K3 (CA). MITCHELL, James, B.; University of Western Ontario, Dept. of Physics, London, Ontario N6A 3K7 (CA). (74) Agents: HUNT, John, F. et al.; Exxon Chemical Company, P.O. Box 2149, Baytown, TX 77522-2149 (US).		(81) Designated States: AU, CA, JP, KR, NO, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: LOW SMOKE COMPOSITION AND FIREFIGHTER TRAINING PROCESS		
(57) Abstract A low smoke firefighter training hydrocarbon composition and process. The compositions preferably contain alkanes and avoid aromatics. Ferrocene or certain other volatile iron compounds are incorporated in the compositions which are readily ignitable but not dangerously so. The process enhances firefighter training while reducing smoke and soot to the surrounding environment.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

**LOW SMOKE COMPOSITION AND
FIREFIGHTER TRAINING PROCESS**

This invention relates generally to a liquid composition usable in firefighter training. The composition, upon combustion, produces low levels of soot and other environmentally undesirable combustion products. Firefighters need to be trained in the skills and equipment for combating large fires. Fire training at major airports servicing commercial airlines needs to be particularly intensive because of the potential severity of jet fuel fires and the short time available to rescue aircraft crash victims. Training programs are carried out at military bases, civilian airports, commercial fire training schools such as Texas A&M University, Lambton College, in Sarnia, Ontario, as well as at a multitude of private, less formal training facilities.

One of the serious problems associated with the training schools, particularly those involving large training fires, is the amount of smoke, soot, and contaminants generated by the fires. Such training fires are not only objectionable from an environmental standpoint, but also present a nuisance for the firefighters as well as residents in the area.

As described and claimed herein, the present invention involves a unique liquid composition useful in fire training activities. The composition upon combustion produces low levels of smoke, soot, and other undesirable combustion products.

Soot, particulate, and chemical emissions from the combustion of fuels in various engines and other enclosed or controlled environments has been the topic of extensive investigation. The prior art in this area teaches us that the use of ferrocene in typically small proportions (up to 10,000 ppm) in liquid hydrocarbon fuels, including diesel fuels, materially improves the ignition and combustion characteristics of the fuels, decreasing their tendency to form soot in the exhaust gases and solid carbonaceous deposits in the engine.


US-A-4908045, 4998876, UK1477806, and EPA 0359390 disclose the use of ferrocene as a fuel additive. However, because the deliberate combustion of liquid hydrocarbon fuels in open, unwicked, and comparatively uncontrolled environments is a relatively uncommon practice, there has been very limited investigation of the products of combustion or their control or limitation. Furthermore, this practice has not been the subject of significant regulation beyond the control of either carrying out the practice. Examples of such activities include slash burning in the forest industry, in-situ burning of crude oil spills [see "Smoke Reduction from Burning Crude Oil Using Ferrocene and its Derivatives", by the Combustion Industry, published in 1991 by Elsevier Science Publishing Co., Inc., pages 179-184 (1991)], and the burning of fuels for firefighter training. In this latter case of burning fuels for firefighter training, the increasing constraints around carrying out the practice have required the industry that provides fire fighting services to pursue other more costly means to provide firefighters adequate training. This invention provides a low cost alternative.

The invention is a low smoke composition comprising a liquid hydrocarbon, said composition having a flash point of 20-125°F and a smoke point of at least 50 mm. The invention is also a process comprising training firefighters with an ignited hydrocarbon composition having a smoke point of at least 50 mm. The smoke point is determined by ASTM method # D 1322-90 Section 5.1. It has surprisingly been discovered that a liquid composition comprising a paraffinic liquid hydrocarbon containing an effective amount of a volatile iron compound, when burned in an open flame, generates extremely low smoke, soot, and other undesirable combustion products, making it ideally suited for fire training activities.

In a preferred embodiment, the liquid composition comprises: (a) a substantially paraffinic liquid hydrocarbon (i.e. at least 75 wt. % of which is a normal alkane or normal alkane mixture containing from 6 to 16 carbon atoms); and (b) an effective amount of a volatile iron compound dissolved or dispersed in the liquid hydrocarbon. The volatile iron compound is selected from the group consisting of iron pentacarbonyl, ferrocene, and ferrocene derivatives.

In another preferred embodiment, the composition contains from 0.1 to 10 wt.%, preferably from 0.2 to 5 wt.% of the volatile iron compound, and will be composed of at least 90%, and most preferably 95 wt.% of the normal alkane constituents. The flash point (TCC) of the liquid hydrocarbon will depend on several factors, but flash points in the range of 0°F to 200°F should be satisfactory for most applications. Preferred flash point ranges are 30°F to 160°F, and 50°F to 150°F. Most preferred is 20°F to 125°F. The liquid composition may be used in firefighter training involving the steps of depositing the composition in an open pit or basin or container, igniting the composition, and conducting fire fighting drills using the flame resulting from burning the composition. According to the present invention, the chemical composition, when introduced, by whatever means, into an open pit or bermed area and ignited for the purpose of training firefighters, is useful in reducing the amount of soot and unsightly black smoke while at the same time providing the advantage in improving the overall air quality through the reduction in the quantities of polycyclic aromatic hydrocarbons (or polynuclear aromatics, PNA's) and volatile organic compounds. The chemical hydrocarbon composition preferably comprises a volatile iron compound and a liquid hydrocarbon which is low, and preferably substantially free of aromatic constituents. Aromatics content in the hydrocarbon composition and process of the invention are preferably below 1.0 wt% of the composition, more preferably below 0.1 wt%. Some suitable compositions contain as low as 0.001-0.0001 wt% aromatics.

While the volatile iron compound may be iron pentacarbonyl $\text{Fe}(\text{CO})_5$, a ferrocene compound is preferred. The ferrocene compound including ferrocene derivatives may be represented by the following formula I:




5 wherein each $R_1, R_2, R_3, R_4, R_5, R_6, R_7, R_8, R_9, R_{10}$, independent of the others, is selected from the group consisting of hydrogen, alkyl, cycloalkyl, aryl, or heterocyclic functional groups. The derivative is preferably selected such that its volatility allows it to be consumed in the burning process at a rate comparable to that of the linear hydrocarbon mixture. The ferrocene derivatives include
 10 di(indenyl)iron.

In the above formula, the term "alkyl" refers to an alkyl group branched or straight chain of 1 to 10 carbon atoms, such as methyl, ethyl, propyl, n-butyl, t-butyl, hexyl, or heptyl. The term "cycloalkyl" refers to lower cycloalkyl groups of 5 to 7 carbon atoms, such as cyclopentyl, cyclohexyl or methyl
 15 cyclohexyl. The term "aryl" refers to an organic radical derived from an aromatic compound by the removal of one hydrogen atom. Such compounds include phenyl, and substituted phenyl such as lower alkyl substituted phenyl. These compounds include tolyl, ethylphenyl, triethylphenyl, halophenyl such as chlorophenyl, and nitrophenyl. The term "heterocyclic" refers to pyrrolyl, pyridyl.

furfuryl, and the like. The aryl or heterocyclic groups generally contain up to about 15 carbon atoms.

The preferred ferrocene and its derivatives have the following formula:



5

where R'_1 and R'_2 are independent and are selected from the group consisting of H and an alkyl group having from 1 to 8 carbon atoms, preferably 1 to 6 carbon atoms, most preferably 1 to 4 carbon atoms. Dicyclopentadienyl iron is commonly referred to as "ferrocene". Hence the compounds of the above formula are considered to be ferrocene and its derivatives. The preferred compounds include dicyclopentadienyl iron, 1, 1'-dimethylcyclopentadienyl iron, 1, 1'-diethylcyclopentadienyl iron, 1, 1'-dibutylcyclopentadienyl and diindenyl ferrocene. These compounds are commercially available and may be prepared by processes well known in the art.

15

In one embodiment, the liquid hydrocarbon is essentially normal paraffinic and may comprise one or more linear alkane constituents. For purposes of the present invention the liquid hydrocarbon may have the following composition and properties:

	Range (wt.%)	Preferred Range (wt.%)	Most Preferred Range (wt.%)
n-alkanes	75 to 100	90 to 100	95 to 100
carbon atoms in n-alkane mixture	C ₆ to C ₁₆	C ₇ to C ₁₄	C ₇ to C ₁₂
aromatic content	less than 1.0	less than 1.0	less than 0.1
other constituents	0 to 25	0 to 10	0 to 5

The ranges specified above are interchangeable. The "other constituents" include isoalkanes and cycloalkanes.

Normal paraffins (n-alkanes) are preferred in the hydrocarbon compositions of the invention. Cycloparaffins are also acceptable but not quite as usable as the normal paraffins. Isoparaffins usually detract from the invention composition, producing somewhat more smoke, but may be present in alkane mixtures.

The invention embodiments include hydrocarbon compositions with small amounts of alkanes, preferably n-alkanes, less preferably cycloalkanes, and less desirably isoparaffins. One embodiment has 10 wt% or more alkanes. The C₈ - C₁₆ alkanes, especially n-alkanes are preferred. The n-alkane and n-alkane mixtures specified above not only produce less soot and other undesirable contaminants, but exhibit the flash point range convenient for fire training. N-alkanes below six carbon atoms are too volatile and are difficult to control and extinguish. N-alkanes above 16 carbon atoms are difficult to ignite and are too easy to extinguish.

The liquid composition may be prepared by dissolving or dispersing the ferrocene compound in the liquid hydrocarbon at a concentration of 0.1 to 10 wt.%, preferably 0.2 to 5 wt.% and most preferably 0.25 to 1.0 wt.%. The solution or dispersion should form a stable uniform composition. The liquid composition may be used in firefighter training by the following process:

- (a) The desired amount of the composition is introduced by whatever means into an open pit or container and/or on a substrate such as wood, concrete, gravel, etc., and/or on another material such as water;
- 5 (b) The composition is ignited and burned until a flame of the desired intensity is reached (with or without introduction of additional liquid composition) ; and
- (c) Firefighting activities are carried out on the flame, the objective of which is generally to extinguish or control the fire for training purposes.
- 10

In distinguishing the present invention over prior art uses of ferrocene in hydrocarbon carriers, it is important to realize that the composition is not generally useful as a commercial fuel or solvent because of limited supply. In fact, tests have demonstrated that commercial fuels and solvents are not suitable

15 because they generate too much soot and other undesirable combustion products. The liquid composition of the present invention is a special formulation having a unique composition and properties, making it ideally suited for fire training uses.

EXAMPLES

Laboratory tests were carried out on various fuels and solvents to

20 determine soot and particulate generation. The test procedure was as follows: A known quantity of fuel or solvent was placed in a crucible and the crucible placed below an inverted funnel system fitted with a filter and attached to a vacuum pump. The fuel or solvent was ignited and all soot and particulates collected on the filter by applying a vacuum to the inverted funnel system. Soot produced is measured by

25 weight and related to the amount of fuel or solvent burned to provide a percent soot.

Table I presents the results using the indicated fuels and solvents, typical of those used in prior firefighter training:

TABLE I

<u>Fuel or Solvent</u>	<u>Wt. % Soot</u>	
	<u>No Ferrocene</u>	<u>With Ferrocene</u>
Jet fuel (JP4)	8.65	5.26 ²
Kerosene	10.12	8.94 ²
Varsol	9.74	8.51 ²
Xylene	16.50	3.49 ²
Toluene	15.50	1.97 ¹

¹ 2 wt. %² 0.25 wt. %

- 5 Similar tests were performed using branched alkanes and cyclic hydrocarbons. The results of these tests are presented in Table II.

TABLE II

<u>Hydrocarbon</u>	<u>Soot (wt. %)</u>	
	<u>No Ferrocene</u>	<u>With Ferrocene</u> ¹
Isooctane	6.23	4.57
Isodecanes and Isoundecanes	4.96	3.21
Isododecanes	4.85	3.20

¹ 0.25 wt. %

- 10 Similar tests were conducted using the liquid composition of one of the embodiment of the present invention. The results are presented in TABLE III.

TABLE III

<u>Composition</u>	<u>Soot (wt. %)</u>	
	<u>No Ferrocene</u>	<u>With Ferrocene</u> ¹
Octane	1.77	1.15
Nonane	1.47	0.85
Decane	1.77	0.86
Dodecane	2.04	0.71
Tetradecane	2.01	0.62
Hexadecane	1.77	0.55

¹ 0.25 wt. %

5 A comparison of the TABLE III data with the data of TABLES I and II reveals the dramatic reduction in soot using the liquid composition of one preferred embodiment the present invention. The comparative results are summarized in TABLE IV.

TABLE IV

<u>Compound</u>	<u>Avg. Soot wt. %</u>	
	<u>No Ferrocene</u>	<u>With Ferrocene</u>
Fuels and Solvents	12.1	6.55
Isoalkanes	5.35	3.66
Composition of present invention	1.85	0.65

10 TABLE IV indicates that the composition of the present invention results in from 88 to 95 wt. % reduction over fuels, solvents, and isoalkanes.

A separate series of larger laboratory experiments, "pool fires", were carried out to determine the nature and quantity of selected non-soot, non-particulate products of combustion. The procedure was as follows. The liquid
 15 material to be burned was placed in a 0.9 meter diameter pan with a 100 mm lip height. The pan was set on a flat platform mounted on a load cell. A hood (2.4

meters by 3.0 meters) was positioned above the pan to collect the combustion products of the pool fire. The bottom edge of the hood was approximately 2.5 meters above the test pan and the hood was connected through a 1.2m² plenum to a 13 meters long 0.56 meter diameter horizontal exhaust duct. The downstream
5 end of the exhaust duct contained a fan with a capacity of at least 2.0 M³/S.

Mass loss of the fuel during the tests was monitored by the load cell. Three sampling ports were installed 9.5 meters downstream from the center of the hood and these were used for taking soot and exhaust gas samples. For each test, 10 kg (approximately 12L) of fuel was used and this was sufficient to allow 10
10 minutes of steady burning.

Soot samples taken from these test burns were subjected to Soxhlet extraction for a period of 48 hours. 150 ml of benzene was used in each case and this was subsequently reduced down to 4 ml following the extractions. Each solution was treated with a deuterated phenanthrene-d10 standard in a
15 concentration of 10 ppm and then equal quantities of each solution were injected into a Gas Chromatograph/Mass Spectrophotometer (GC/MS) for analysis.

TABLE V presents the results of the experiment showing the relative amounts of polycyclic aromatic hydrocarbons (PAH's) found in the soot samples from JP4 jet fuel and a normal paraffin mixture containing ferrocene.

TABLE V

<u>Chemical</u>	<u>JP4</u>	<u>Normal Dodecanes¹</u>	
		<u>+ 1.0 wt. %</u> <u>Ferrocene</u>	<u>%</u> <u>Reduction</u>
Acenaphthalene	1880	496	74
Acenaphthalene	423	98	77
Fluorene	381	172	55
Phenanthrene	9027	1543	83
Anthracene	1200	199	83
Fluoranthrene	8015	302	96
Pyrene	7630	290	96
Benzo(a)anthracene	956	0	100
Chrysene/Triphenylene	1214	231	81
Benzo(b) fluoranthrene	803	0	100
Benzo(k) fluoranthrene	293	0	100
Benzo(e)pyrene	610	133	78
Benzo(a)pyrene	632	0	100
Perylene	0	0	--
Indeno (1,2,3-cd) pyrene	310	0	100
Dibenzo(a,h) anthracene	0	0	--
Benzo(ghi)perylene	419	0	100

¹ mixture of linear hydrocarbons with an average carbon number of 12 but including carbon numbers from 10 to 14.

- 5 As can be seen from the data in TABLE V, the normal paraffin ferrocene mixture provides substantial reductions in the amounts of PAH's produced in the burn process. Overall the normal paraffin-ferrocene mixture provided an average 88% reduction in 3 ring and larger PAH's. Exhaust gas samples taken from the experiment described above were analyzed for volatile

organic compounds and formaldehyde using Tenax tubes and dinitrophenylhydrazine sorption tubes.

TABLE VI presents the results of the experiment showing the volatile organic compounds (VOC's) found in the combustion zone for test burns of JP4 jet fuel and a normal paraffin mixture containing ferrocene.

TABLE VI
Normal Dodecanes¹ +

<u>Chemical</u>	<u>JP4</u>	<u>1.0 wt.% Ferrocene</u>	<u>% Reduction</u>
Benzene	290	10	96
Toluene	48	9	82
Formaldehyde	135	52	62

¹ mixture of linear hydrocarbons with an average carbon number of 12 but including carbon numbers from 10 to 14.

10

As can be seen from the data in TABLE VI, the normal paraffin ferrocene mixture provides substantial reductions in the amounts of VOC's produced in the burn process with a 96% reduction in benzene and an 82% reduction in toluene. The data in TABLE VI also show a 62% reduction in formaldehyde production in the burn process.

One embodiment of the invention combines 0.25-0.5 wt.% ferrocene with a mixed alkane composition of predominantly normal paraffins. Such materials are available from Exxon Chemical Company as Exxsol[®] brand heptane comprising 4 wt.% cycloheptane, less than 0.01 wt.% aromatics and 96 wt.% mixed iso- and n-heptane; plus Norpar[®] brand 12 solvent comprising less than 0.01 wt.% aromatics and 100 % normal paraffins.

In another preferred embodiment of the invention, about 0.25 wt.% ferrocene is combined with a mixed alkane composition of predominantly normal paraffins. Such materials are available from Exxon Chemical Company as Exxsol[®] brand D-40 dearomatized aliphatic having about 42 wt.% normal and iso paraffins, 57 wt.% cycloparaffins and 0.4 wt.% aromatics. Such predominantly normal

25

paraffinic compositions with 0.25 wt.% ferrocene, when ignited in a firefighter training process, exhibit visual smoke ratings of about 3 or less, with a diesel fuel-ferrocene composition exhibiting a 10 rating and the linear hydrocarbon mixture with ferrocene of Table V exhibiting a 1 rating (very low smoke).

5 During the training of firefighters in the art of extinguishment and control of fires in open pits or bermed areas, water is sometimes used in a manner in which it is placed in the pit or bermed area and the liquid to be burned then placed on top of the water and ignited. In such practice, contamination of the water by residual combustion products presents environmental problems and costs
10 are incurred to clean the water prior to its reuse or disposal. In experiments similar to the one described above which were carried out in the presence of water under the burning liquid, substantially less residue was observed from fires using the normal paraffin / ferrocene mixture compared to fires using conventional fuels. Use of the normal paraffin / ferrocene mixture will result in less waste, and lower
15 water treatment and disposal costs.

 The compositions of the invention permit reduced use of volume of composition consumed during training. From the above results, it is clear that the ferrocene / n-paraffin mixture, according to this invention, is unique and superior to conventional fuels and fuel additive combinations because of (a) the extremely low
20 levels of soot and particulate produced during burning; (b) the dramatic reduction in the amount of polycyclic aromatic hydrocarbons produced during burning; (c) the significant reduction in the amount of volatile organic components, especially PNA's, produced during burning; (d) the reduction in the amount of formaldehyde produced during burning; (e) the reduction in the amount of and undesirable nature
25 of the residue left after completion of the burning; (f) reduction of benzene emissions; (g) reduced volatile organics before combustion; and (h) lower ED-50 levels (ED-50 is the effective dilution at which 50% of the population would notice an odor in the atmosphere).

 The invention includes: a liquid composition for use in fire training.
30 which comprises (a) a liquid hydrocarbon containing less than 5 wt. % aromatics,

said liquid hydrocarbon comprising at least 75 wt. % of an n-alkane or a mixture of n-alkanes having from 6 to 16 carbon atoms; and (b) an effective amount of a volatile iron compound dissolved or dispersed in the hydrocarbon liquid to reduce the soot content of the hydrocarbon liquid upon combustion compared with no
5 volatile iron compound in the hydrocarbon liquid, said volatile iron compound being selected from the group consisting of iron pentacarbonyl, ferrocene, and ferrocene derivatives.

The invention also uses the above liquid composition wherein the volatile iron compound is a ferrocene compound, or a ferrocene derivative having
10 formula I wherein the R's are independent of each other and are selected from the group consisting of H, alkyl, cycloalkyl, aryl, and heterocyclic functional groups.


The invention is also the above liquid composition wherein the concentration of the volatile iron compound in the hydrocarbon liquid ranges from 0.1 wt.% to 10 wt.% based on the combined wt. of the liquid and the volatile iron
15 compound; or wherein the hydrocarbon liquid contains less than 1% aromatics and comprises at least 95% of the n-alkanes; or less than 0.1 wt.% aromatics; or both.

The invention uses the above liquid composition wherein the liquid hydrocarbon contains from 0 to 25 wt.% isoparaffins and cycloparaffins.

The invention uses the above liquid composition wherein the liquid
20 hydrocarbon has a flash point of between 0°F and 200°F.

The invention uses a liquid composition for firefighter training which comprises:

- (a) from 95 to 99.9 wt.% of a liquid hydrocarbon containing less than 1 wt.% aromatics and being composed of from 90 to
25 100% of an n-alkane or n alkane mixture having from 6 to 16 carbon atoms, said liquid hydrocarbon having a flash point of between 30 and 150°F; and
- (b) from 0.1 to 5 wt.% of ferrocene compound having the following formula:



where R'₁ and R'₂ are independent of each other and are selected from the group consisting of H and an alkyl group having from 1 to 8 carbon atoms, or wherein the above liquid hydrocarbon contains less than 0.1 wt.% aromatics; or wherein the composition upon combustion produces less than 1.0 wt.% soot, or both.

The invention is also the above composition wherein the n-alkane has an average carbon number of between 7 and 14, preferably 8 to 12.

The invention is also a fire training method which comprises:

- (a) introducing by whatever means one of the above liquid compositions into an open pit or container;
- (b) igniting the liquid composition and permitting it to burn to the desired flame intensity;
- (c) carrying out fire training activities on the flame, or wherein the liquid composition is disposed on water in the pit or container, or wherein the burning of the liquid composition produces less than 1.0 wt.% soot.

Claims:

We Claim:

1. A low smoke composition comprising a liquid hydrocarbon, said
5 composition having a flash point of 20-125°F and a smoke point of at least 50 mm.
2. The composition of claim 1 containing a volatile iron compound
selected from iron pentacarbonyl, ferrocene, and ferrocene derivatives.
- 10 3. The composition of claim 2 wherein the volatile iron compound is a
ferrocene compound or derivative of formula I wherein the R's are independently
selected from H, alkyl, cycloalkyl, aryl, and heterocyclic functional groups.
4. The composition of claim 2 wherein said volatile iron compound is
15 present at 0.1 - 10.0 wt.%.
5. The composition of claim 1 comprising less than 1.0 wt.%
aromatics.
- 20 6. The composition of claim 5 comprising less than 0.1 wt.%
aromatics.
7. The composition of claim 5 containing a volatile iron compound
selected from iron pentacarbonyl, ferrocene, and ferrocene derivatives.
25
8. The composition of claim 1 comprising at least 10 wt.% of one or
more alkanes.
9. The composition of claim 8 comprising at least 75 wt.% of said
30 alkanes.

10. The composition of claim 8 wherein said alkanes are n-alkanes or cycloalkanes.
- 5 11. The composition of claim 8 wherein said alkanes are C₈-C₁₆.
12. The composition of claim 8 containing a volatile iron compound selected from iron pentacarbonyl, ferrocene, and ferrocene derivatives.
- 10 13. The composition of claim 8 comprising less than 1.0 wt.% aromatics.
14. The composition of claim 12 comprising less than 1.0 wt.% aromatics.
- 15 15. The composition of claim 1 producing upon combustion, soot in an amount less than 1.0 wt.% of the composition consumed.
16. A process comprising training firefighters with an ignited hydrocarbon composition having a smoke point of at least 50 mm.
- 20 17. The process of claim 16 wherein said composition has a flash point of 20-125°F.
- 25 18. The process of claim 16 comprising:
- (a) introducing said composition into an open pit or container;
 - (b) igniting and burning the composition to the desired flame intensity; and
 - (c) conducting fire training activities on the flame.

30

19. The process of claim 16 wherein the burning composition produces soot in an amount less than 1.0 wt.% of the composition consumed.

20. The process of claim 16 wherein said composition contains a
5 smoke-reducing amount of a volatile iron compound.

21. The process of claim 16 wherein said composition comprises at least 10 wt.% alkanes.

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/US 96/19915

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C10L1/30 C10L10/02 G09B9/00 A62C39/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 C10L G09B A62C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 010, no. 185 (C-357), 27 June 1986 & JP 61 031492 A (IDEMITSU PETROCHEM CO LTD), 13 February 1986, see abstract ---	1-15
A	US 3 644 073 A (GOLDSMITH) 22 February 1972 see the whole document ---	16-19
A	US 4 908 045 A (FARRAR) 13 March 1990 cited in the application see column 4 ---	1-15
A	EP 0 359 390 A (VELINO VENTURES) 21 March 1990 cited in the application see the whole document ---	1-15
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

18 April 1997

Date of mailing of the international search report

28.04.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

De La Morinerie, B

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/US 96/19915

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 25 02 307 A (SYNTEX) 31 July 1975 cited in the application see page 13 - page 16; examples 1-4 ---	1-15
A	DATABASE WPI Section Ch, Week 7949 Derwent Publications Ltd., London, GB; Class E12, AN 79-88876B XP002029784 & SU 652 944 A (FIRE DEFENCE RES) , 28 March 1979 see abstract -----	1-15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 96/19915

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3644073 A	22-02-72	NONE	
US 4908045 A	13-03-90	AU 627260 B	20-08-92
		AU 4729289 A	28-06-90
		CA 2005269 A	23-06-90
		EP 0375303 A	27-06-90
		JP 2242887 A	27-09-90
EP 359390 A	21-03-90	AU 627760 B	03-09-92
		AU 3958489 A	15-02-90
		CA 1322453 A	28-09-93
		JP 2132188 A	21-05-90
		US 4998876 A	12-03-91
DE 2502307 A	31-07-75	CH 611335 A	31-05-79
		FR 2273059 A	26-12-75
		GB 1477806 A	29-06-77
		GB 1477807 A	29-06-77
		JP 50123703 A	29-09-75
		NL 7500705 A	23-07-75
		SE 7500580 A	22-07-75

THIS PAGE BLANK (USPTO)